



| Model | Power | Luminous flux | Dimensions | Cut-out | Input | Chip led |
|--------|-------|---------------|-------------|----------|----------|----------|
| A0510T | 5*2w | 800lm | 149*70*50mm | 140*37mm | 200-240V | OSRAM |

| | | | | | | | | | | | | |
|---------------|---------------|--------------|------------|------------|----------|----------|------|-------|-------|-----|-----|-----|
| TRIAC Dimming | 0-10V Dimming | DALI Dimming | No Flicker | Anti Glare | CRI > 90 | < 3 SDCM | IP20 | 3000K | 4000K | 15° | 30° | 45° |
|---------------|---------------|--------------|------------|------------|----------|----------|------|-------|-------|-----|-----|-----|

| Cut-out 140x37 | | | | 15° | | | 30° | | | 45° | | |
|----------------|--------|-------|------|--------|-------|------|--------|-------|------|--------|-------|--|
| H(m) | E(lux) | D(cm) | H(m) | E(lux) | D(cm) | H(m) | E(lux) | D(cm) | H(m) | E(lux) | D(cm) | |
| 1 | 8536 | 32 | 1 | 4667 | 55 | 1 | 3198 | 65 | 1 | 3198 | 65 | |
| 2 | 2134 | 65 | 2 | 1164 | 110 | 2 | 799 | 130 | 2 | 799 | 130 | |
| 3 | 948 | 97 | 3 | 517 | 166 | 3 | 355 | 196 | 3 | 355 | 196 | |
| 4 | 553 | 130 | 4 | 291 | 221 | 4 | 199 | 261 | 4 | 199 | 261 | |
| 5 | 341 | 162 | 5 | 186 | 277 | 5 | 127 | 327 | 5 | 127 | 327 | |